

The Aerus® Pure & Clean+ reduced 99.96% of airborne SARS-CoV-2, the virus responsible for COVID-19, within 1 minute.*

This unaffiliated lab test was done on the lowest setting using only the ActivePure® Technology.

THE TECHNOLOGY

The Aerus® Pure & Clean+ combines multiple complementary technologies, including HEPA, activated carbon, O³, and ActivePure Technology. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:1

- SARS-CoV-2
- Staphylococcus aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- · Erwinia herbicola

- Listeria
 monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- · Aspergillus versicolor
- · Clostridium difficile
- Salmonella enterica

THE BENEFITS

The Aerus Pure & Clean+ provides 24/7 surface decontamination and air purification. It is a proactive and effective solution for your home or business.

- · Portable, lightweight device
- No installation plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi¹
- Reduces smoke, allergens, odors, and VOC gases
- Multiple carbon brushes aid in the capture of contaminants







Inducted into the 2017 Space Technology Hall of Fame by the Space Foundation



¹View test results at ActivePure.com/scientific-proof



SPECIFICATIONS

31 ECH ICATIONS	
Product Information	00747 Model: A1041A NOTE: This product does not meet California requirements and cannot be shipped to California or Canada.
Technology Included	ActivePure® Technology (1 cell) HEPA Filter Screen Activated Carbon Filter Carbon Brushes Purification Plate
Electrical	Input Voltage: 100-240 VAC; 50/60 Hz External Power Supply: DC 24 Volts; 1.5 Amps Max Power Consumption: 43 Watts Max.
Safety	Conforms to UL 867
Mechanical	Nominal Airflow Rate: 40-60 CFM Adjustable Fan Speed
Weight & Dimensions	7.6 lbs (3.5 kg) 11.75" H x 9.5" W x 10" D (29.8 cm x 24.1 cm x 25.4 cm)
Operating Temperature	34°F - 100°F (-1°C - 38°C)
Sound Level	45 dB(A) (on low); 55dB(A) (on high)
Coverage ¹	Up to 2,000 sq. ft. (185 m²) depending on occupant density and other factors.¹ High density commercial not to exceed 500 sq. ft. (46 m²).
Warranty	Limited 3 year warranty

Contact Name:
 Email:



^{1.} Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.

